


## GLV-40 BRONZE HOT LINE CLAMP

This specification details the product GLV-40 Hot Line Clamp, developed for overhead primary tap, AAC|AAAC|ACSR|Copper, range 0.128 - 0.563 in

### Features

- Designed to provide a reliable connection on energized conductors, ensuring safety and efficiency in electrical maintenance and operation.
- Lock washer technology (tap), ensuring that no stress relaxation occurs.



Representative image

| General                |                 |
|------------------------|-----------------|
| Material - Body        | Bronze          |
| Material - Keeper      | Aluminum bronze |
| Material - Eye stem    | Aluminum bronze |
| Material - Eye bolt    | Aluminum bronze |
| Material - Hex nut     | Bronze alloy    |
| Material - Lock washer | Bronze alloy    |

| Dimensions |                             |
|------------|-----------------------------|
| Dimensions | 2.35 in x 1.82 in x 5.92 in |
| Height     | 5.92 in                     |
| Length     | 2.35 in                     |
| Weight     | 0.843 lb                    |
| Width      | 1.82 in                     |

| Electrical Ratings |                           |
|--------------------|---------------------------|
| Rated current      | 400 A                     |
| Rated voltage      | Up to and including 36 kV |
| Frequency          | 50/60 Hz                  |

| Conductor Related       |                                                                                                                                                                                                                                                                                                  |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Conductor compatibility | <b>Main:</b> ACSR-Turkey-6 / ACSR Swan- 4 / ACSR-Swanete-4 / ACSR-Sparrow-2 / ACSR-Sparate- 2 / ACSR-Robin-1 / ACSR-Raven- 1/0 / ACSR-Quail-2/0 / ACSR Pigeon- 3/0 / ACSR-Penguin-4/0 / AAC-Rose-4 / AAC-Iris-2 / AAC Pansy- 1 / AAC-Poppy-1/0 / AAC Aster- 2/0 / AAC-Phlox-3/0 / AAC Oxlip- 4/0 |

|  |                                                                                                                                                                                                                         |
|--|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <b>Tap:</b> ACSR-Turkey-6 / ACSR Swan- 4 / ACSR-Swanete-4 / ACSR-Sparrow-2 / ACSR-Sparate- 2 / ACSR-Robin-1 / ACSR-Raven- 1/0 / AAC-Peachbell-6 / AACRose- 4 / AAC-Iris-2 / AAC-Pansy-1 / AAC-Poppy-1/0 / AAC-Aster-2/0 |
|--|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                     |                  |
|-------------------------------------|------------------|
| Conductor Diameter (Tap) - Maximum  | 0.440 in         |
| Conductor Diameter (Tap) - Minimum  | 0.128 in         |
| Conductor Diameter (Main) - Maximum | 0.563 in         |
| Conductor Diameter (Main) - Minimum | 0.128 in         |
| Conductor Diameter Range (Tap)      | 0.128 - 0.440 in |
| Conductor Diameter Range (Main)     | 0.128 - 0.563 in |

| Logistics      |     |
|----------------|-----|
| Packaging Type | Box |

### Product Assets

Technical catalog of products  
Sales Drawing - 3031430002  
Specification - 3031430002